SAFETY DATA SHEET

1. Identification

Product identifier POWER CUT PLUS

Other means of identification

110 **Product Code**

Compound, Polishing Creme Recommended use

None known. **Recommended restrictions**

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Malco Products, Inc. Company name 361 Fairview Ave **Address** Barberton, OH 44203

United States

Phone 800-253-2526 **Telephone**

Fax 330-777-8317

Website www.malcopro.com E-mail msdsinfo@malcopro.com **Technical Department Contact person**

Phone **Emergency phone number** 1-800-424-9300

2. Hazard(s) identification

Physical hazards Flammable liquids Category 4

Health hazards Acute toxicity, oral Category 5

Acute toxicity, inhalation Category 5 Serious eye damage/eye irritation Category 2A Sensitization, skin Category 1 Category 2

Specific target organ toxicity, repeated

exposure

Aspiration hazard Category 1

Environmental hazards Hazardous to the aquatic environment, acute Category 3

hazard

Hazardous to the aquatic environment, Category 3

long-term hazard

OSHA defined hazards Not classified.

Label elements





Combustible liquid. May be harmful if swallowed. Causes serious eye irritation. May be harmful if **Hazard statement**

inhaled. May cause damage to organs through prolonged or repeated exposure.

Precautionary statement

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe mist or Prevention

vapor. Wash thoroughly after handling. Wear protective gloves/eye protection/face protection.

IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell. If in eyes: Rinse Response

cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get

medical advice/attention. In case of fire: Use appropriate media to extinguish.

Storage Store in a well-ventilated place. Keep cool.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Material name: POWER CUT PLUS

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Aluminum Oxide; Alumina		1344-28-1	30 - < 40
Solvent Naphtha (Petroleum), Medium Aliph.		64742-88-7	10 - < 20
Glycerol		56-81-5	5 - < 10
KEROSENE		8008-20-6	5 - < 10
"1,3-Bis(hydroxymethyl)-5,5-dimeth ylimidazolidine-2,4-dione"		6440-58-0	< 0.2
Sodium Hydroxide		1310-73-2	< 0.1
Tetrasodium Pyrophosphate		7722-88-5	< 0.1
Other components below reportable	e levels		40 - < 50

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

InhalationIf breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Get medical advice/attention if you feel unwell.

Most important symptoms/effects, acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards Combustible liquid.

_ _

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.

Material name: POWER CUT PLUS

110 Version #: 01 Issue date: 09-19-2025

Methods and materials for containment and cleaning up

Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Keep away from open flames, hot surfaces and sources of ignition. Do not breathe mist or vapor. Do not taste or swallow. Avoid contact with eyes. Avoid prolonged exposure. When using, do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers.

8. Exposure controls/personal protection

Occupational exposure limits

Components	r Contaminants (29 CFR 1910.1000) Type	Value	Form
Aluminum Oxide; Alumina (CAS 1344-28-1)	PEL	5 mg/m3	Respirable fraction.
,		15 mg/m3	Total dust.
Glycerol (CAS 56-81-5)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Sodium Hydroxide (CAS 1310-73-2)	PEL	2 mg/m3	
US. ACGIH Threshold Limit Value	es		
Components	Туре	Value	Form
KEROSENE (CAS 8008-20-6)	TWA	200 mg/m3	Non-aerosol.
Sodium Hydroxide (CAS 1310-73-2)	Ceiling	2 mg/m3	
US. NIOSH: Pocket Guide to Cher	mical Hazards		
Components	Туре	Value	
KEROSENE (CAS 8008-20-6)	TWA	100 mg/m3	
Sodium Hydroxide (CAS 1310-73-2)	Ceiling	2 mg/m3	
Tetrasodium Pyrophosphate (CAS 7722-88-5)	TWA	5 mg/m3	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

US ACGIH Threshold Limit Values: Skin designation

KEROSENE (CAS 8008-20-6)

Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection

Material name: POWER CUT PLUS

110 Version #: 01 Issue date: 09-19-2025

Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear suitable protective clothing. Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid.

Form Liquid. Viscous. Cream.

Color Tan

Odor Slight Kerosene
Odor threshold Not available

pH 8.2

Melting point/freezing point 2843.48 °F (1561.94 °C) estimated initial boiling point and boiling 3736.76 °F (2058.2 °C) estimated

range

Flash point 145.0 °F (62.8 °C) estimated

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

0.7 % estimated

(%)

Flammability limit - upper

5 % estimated

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 0.05 hPa estimated

Vapor density

Not available.

Relative density

Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.Viscosity220,000 cPViscosity temperature68 °F (20 °C)

Other information

Density 10.60 lbs/gal

Flammability class Combustible IIIA estimated

VOC 16.95 %

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

ossibility of hazardous Hazardous polymenzation does not occu

Material name: POWER CUT PLUS

110 Version #: 01 Issue date: 09-19-2025

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials

Strong oxidizing agents. Chlorine.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

May be harmful if inhaled. May cause damage to organs through prolonged or repeated exposure Inhalation

by inhalation.

Skin contact No adverse effects due to skin contact are expected.

Eye contact Causes serious eye irritation. Ingestion May be harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision. Skin irritation.

Information on toxicological effects

May be harmful if inhaled. Acute toxicity

Test Results Components **Species**

"1,3-Bis(hydroxymethyl)-5,5-dimethylimidazolidine-2,4-dione" (CAS 6440-58-0)

Acute Oral

LD50 Rat 2 g/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not available.

This product is not expected to cause skin sensitization. Skin sensitization

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Not available. **Aspiration hazard**

Chronic effects May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may

be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

110 Version #: 01 Issue date: 09-19-2025

Components Species Test Results

Glycerol (CAS 56-81-5)

Aquatic

Fish LC50 Rainbow trout, donaldson trout 51000 - 57000 mg/l, 96 hours

(Oncorhynchus mykiss)

Sodium Hydroxide (CAS 1310-73-2)

Aquatic

Fish LC50 Western mosquitofish (Gambusia affinis) 125 mg/l, 96 hours

Tetrasodium Pyrophosphate (CAS 7722-88-5)

Aquatic

Fish LC50 Western mosquitofish (Gambusia affinis) 1380 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

Glycerol -1.76

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulationsDispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packagingSince emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not available.

the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

One or more components are not listed on TSCA.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Sodium Hydroxide (CAS 1310-73-2) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

categories

SARA 311/312 Hazardous

chemical

Yes

Classified hazard

Flammable (gases, aerosols, liquids, or solids)

Acute toxicity (any route of exposure) Serious eye damage or eye irritation

Respiratory or skin sensitization

Specific target organ toxicity (single or repeated exposure)

Aspiration hazard

SARA 313 (TRI reporting)

Chemical name CAS number % by wt. Aluminum Oxide; Alumina 1344-28-1 30 - < 40

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Glycerol (CAS 56-81-5)

Other Flavoring Substances with OSHA PEL's

US state regulations

California Proposition 65

WARNING: California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material

is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

KEROSENE (CAS 8008-20-6) Sodium Hydroxide (CAS 1310-73-2)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Toxic Chemical Substances (TCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

country(s).

16. Other information, including date of preparation or last revision

09-19-2025 Issue date

Version # 01

SDS US

Material name: POWER CUT PLUS 7/8 110 Version #: 01 Issue date: 09-19-2025

Disclaimer

Malco Products, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision information

Hazard(s) identification: GHS Signal Words

Composition / Information on Ingredients: Ingredients Physical & Chemical Properties: Multiple Properties

Toxicological information: Inhalation

GHS: Classification