

SAFETY DATA SHEET

1. Identification

Product identifier SHIELDPRO UV CREME WAX

Other means of identification

1661 **Product Code**

Recommended use Vehicle Wax **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Malco Products, Inc. **Address** 361 Fairview Ave Barberton, OH 44203

United States

Phone 800-253-2526 **Telephone** 330-753-2025 Fax

www.malcopro.com

Website msdsinfo@malcopro.com E-mail **Technical Department** Contact person

1-800-424-9300 Phone **Emergency phone number**

Not available. **Supplier**

2. Hazard identification

Physical hazards Flammable liquids Category 4 **Health hazards** Serious eye damage/eye irritation Category 2B Specific target organ toxicity, repeated Category 2

exposure

Environmental hazards Not classified.

Label elements



Signal word

Hazard statement Combustible liquid. May be harmful if swallowed. Causes eye irritation. May cause damage to organs

through prolonged or repeated exposure.

Precautionary statement

Prevention Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do

not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this

product. Wear protective gloves/protective clothing/eye protection/face protection.

Get medical advice/attention if you feel unwell. If eye irritation persists: Get medical advice/attention. Response

In case of fire: Use appropriate media to extinguish.

Store in a well-ventilated place. Store away from incompatible materials. **Storage**

Dispose of contents/container in accordance with local/regional/national/international regulations. Disposal

Supplemental information None.

Other hazards None known.

3. Composition/information on ingredients

Mixtures

Material name: SHIELDPRO UV CREME WAX 1/7

1661 Version #: 06 Revision date: 11-05-2025 Issue date: 10-30-2025

Chemical name	Common name and synonyms	CAS number	%
Solvent Naphtha (Petroleum), Medium Aliph.		64741-65-7	10 - < 20
Distillates (Petroleum), Hydrotreated Light		64742-47-8	5 - < 10
Bentonite Clay		14808-60-7	1 - < 3
Other components below reportable	levels		70 - < 80

DSD: Directive 67/548/EEC. CLP: Regulation No. 1272/2008.

#: This substance has been assigned Community workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume. *Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Composition comments

The full text for all R- and H-phrases is displayed in section 16.

4. First-aid measures

InhalationMove to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a

one-way valve or other proper respiratory medical device. Call a physician if symptoms develop or

persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists. For minor skin

contact, avoid spreading material on unaffected skin.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial

respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory

medical device. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

In case of shortness of breath, give oxygen. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Keep victim under observation. Keep victim warm.

5. Fire-fighting measures

Suitable extinguishing media Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from The pro

the chemical

Special protective equipment

The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.

ent Self-conta

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

and precautions for firefighters Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions. ALWAYS stay away from tanks engulfed in flame. Move containers from fire area if you can do so without risk. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards Combustible liquid.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into

drains, water courses or onto the ground.

Type

Environmental precautions

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. All equipment used when handling the product must be grounded. Do not breathe mist or vapor. Do not taste or swallow. Avoid contact with eyes. Avoid contact with skin. Avoid prolonged exposure. When using, do not eat, drink or smoke. Do not use in areas without adequate ventilation. Wear appropriate personal protective equipment. Wash thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

Value

Form

8. Exposure controls/personal protection

Occupational exposure limits

Componento

211	ACGIH	Threshold	Limit	Values	/TI V/
UJ.	ACGIN	HIHESHOIU	LIIIII	values	(I L V)

•	Туре	Value	Form
Bentonite Clay (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Canada. Alberta OELs (Occupa	ational Health & Safety Code, Sch	nedule 1, Table 2), as amended	
Components	Туре	Value	Form
Bentonite Clay (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable particles.
Canada. Manitoba OELs (Reg.	217/2006, The Workplace Safety	And Health Act), as amended	
Components	Туре	Value	Form
Bentonite Clay (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Canada. New Brunswick OELs Publication (New Brunswick R	: Threshold Limit Values (TLVs) I	Based on the 1991 and 1997 AC	CGIH TLVs and BEIs
•	egulation 91-191)		_
•	Type	Value	Form
Components Bentonite Clay (CAS	_ ′	Value 0.025 mg/m3	Form Respirable fraction.
Components Bentonite Clay (CAS 14808-60-7)	Type TWA	0.025 mg/m3	Respirable fraction.
Components Bentonite Clay (CAS 14808-60-7) Canada. Ontario OELs (Regula	Туре	0.025 mg/m3	Respirable fraction.
Components Bentonite Clay (CAS 14808-60-7) Canada. Ontario OELs (Regula Components	Type TWA ation 833, Control of Exposure to	0.025 mg/m3 Biological or Chemical Agents	Respirable fraction.
Components Bentonite Clay (CAS 14808-60-7) Canada. Ontario OELs (Regula Components Bentonite Clay (CAS 14808-60-7)	Type TWA ation 833, Control of Exposure to Type TWA	0.025 mg/m3 Biological or Chemical Agents Value 0.1 mg/m3	Respirable fraction. s), as amended Form Respirable fraction.
Components Bentonite Clay (CAS 14808-60-7) Canada. Ontario OELs (Regula Components Bentonite Clay (CAS 14808-60-7)	Type TWA ation 833, Control of Exposure to Type	0.025 mg/m3 Biological or Chemical Agents Value 0.1 mg/m3	Respirable fraction. s), as amended Form Respirable fraction.
Components Bentonite Clay (CAS 14808-60-7) Canada. Ontario OELs (Regula Components Bentonite Clay (CAS 14808-60-7) Canada. Quebec OELs (Regula	Type TWA ation 833, Control of Exposure to Type TWA ation respecting occupational hea	0.025 mg/m3 Biological or Chemical Agents Value 0.1 mg/m3 alth and safety, v. S-2.1, r.13), a	Respirable fraction. s), as amended Form Respirable fraction.

Material name: SHIELDPRO UV CREME WAX 3/7 Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996; Table 21), as amended Components

Type

Value

Form

Bentonite Clay (CAS 8 hour 0.05 mg/m3 Respirable fraction.

14808-60-7)

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Ensure adequate ventilation, especially in confined areas. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear suitable protective clothing. Use of an impervious apron is recommended. Wear protective

gloves.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Physical state Liquid

Form Liquid. Viscous.

ColorYellow.OdorBananaMelting point/freezing pointNot available.

Boiling point or initial boiling

point and boiling range

211.95 °F (99.97 °C) estimated

Flammability Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Flash point >145.0 °F (>62.8 °C)

Auto-ignition temperature

Decomposition temperature

pH

Not available.

Not available.

Not available.

Not available.

Solubility

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water) (log value)

Vapor pressure -0.01 hPa estimated

Density and/or relative density

Density8.16 lbs/galVapor densityNot available.Particle characteristicsNot available.

Other information

Explosive properties Not explosive.

Flammability class Combustible IIIA estimated

Oxidizing properties Not oxidizing.

Material name: SHIELDPRO UV CREME WAX

1661 Version #: 06 Revision date: 11-05-2025 Issue date: 10-30-2025

Viscosity 25000 cP VOC 14 % by weight

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash

point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause damage to organs through prolonged or repeated exposure by inhalation.

Skin contact No adverse effects due to skin contact are expected.

Eye contact Causes eye irritation.

Ingestion May be harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Information on toxicological effects

Acute toxicity Not available.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are mutagenic

or genotoxic.

Carcinogenicity

ACGIH Carcinogens

Bentonite Clay (CAS 14808-60-7) A2 Suspected human carcinogen.

Canada - Alberta OELs: Carcinogen category

Bentonite Clay (CAS 14808-60-7) Suspected human carcinogen.

Canada - Manitoba OELs: carcinogenicity

Bentonite Clay (CAS 14808-60-7) Suspected human carcinogen.

Canada - Quebec OELs: Carcinogen category

Bentonite Clay (CAS 14808-60-7)

Suspected carcinogenic effect in humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Bentonite Clay (CAS 14808-60-7) 1 Carcinogenic to humans.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Chronic effects May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be

harmful. Prolonged exposure may cause chronic effects.

Material name: SHIELDPRO UV CREME WAX

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Species Test Results

Distillates (Petroleum), Hydrotreated Light (CAS 64742-47-8)

Aquatic

Acute

Fish LC50 Rainbow trout, donaldson trout

(Oncorhynchus mykiss)

2.9 mg/l, 96 hours

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product

residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

TDG

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

Not established.

15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Material name: SHIELDPRO UV CREME WAX

SDS CANADA

^{*} Estimates for product may be based on additional component data not shown.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region Inventory name On inventory (yes/no)* Canada

Domestic Substances List (DSL) Yes Non-Domestic Substances List (NDSL) Canada No

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

10-30-2025 Issue date 11-05-2025 **Revision date**

Version # 06

References **ACGIH**

EPA: AQUIRE database

NLM: Hazardous Substances Data Base

US. IARC Monographs on Occupational Exposures to Chemical Agents

Malco Products, Inc. cannot anticipate all conditions under which this information and its product, or Disclaimer

the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality

specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and experience currently

available.

This document has undergone significant changes and should be reviewed in its entirety. **Revision information**

Material name: SHIELDPRO UV CREME WAX 7/7

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)