SAFETY DATA SHEET

1. Identification

Product identifier Marine Super Cut Compound

Other means of identification

1674 **Product Code**

Recommended use Compound, Polishing Creme

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Malco Products, Inc. **Address** 361 Fairview Ave Barberton, OH 44203

United States

Phone 800-253-2526 Telephone 330-753-2025 Fax

Website www.malcopro.com msdsinfo@malcopro.com E-mail

Technical Department Contact person

1-800-424-9300 Phone **Emergency phone number**

Not available. **Supplier**

2. Hazard identification

Physical hazards Flammable liquids Category 4 **Health hazards** Acute toxicity, oral Category 5 Acute toxicity, inhalation Category 5 Serious eye damage/eye irritation Category 2A Specific target organ toxicity, repeated Category 2

exposure

Environmental hazards Not classified.

Label elements



Signal word Warning

Hazard statement May be harmful if inhaled. Combustible liquid. Causes serious eye irritation. May cause damage to

organs through prolonged or repeated exposure.

Precautionary statement

Prevention Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Protect from sunlight. Do not breathe mist/vapors. Wash thoroughly after handling. Use only outdoors

or in a well-ventilated area. Wear eye protection/face protection.

IF ON SKIN: Wash with plenty of water. IF INHALED: Remove person to fresh air and keep Response

comfortable for breathing. Call a POISON CENTER/doctor. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use

appropriate media to extinguish.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up. Store away from

incompatible materials.

Dispose of waste and residues in accordance with local authority requirements. Dispose of **Disposal**

contents/container in accordance with local/regional/national/international regulations.

Material name: Marine Super Cut Compound 1/8

1674 Version #: 08 Revision date: 11-04-2025 Issue date: 04-18-2023

Supplemental information

55.3383735% of the mixture consists of component(s) of unknown acute dermal toxicity. 56.84% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 56.84% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

Other hazards None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Solvent Naphtha (Petroleum), Medium Aliph.		64742-88-7	10 - < 20
KEROSENE		8008-20-6	5 - < 10
propane-1,2,3-triol		56-81-5	5 - < 10
4-nonylphenol, Branched, Ethoxylated		127087-87-0	1 - < 3
Other components below reportable	e levels		70 - < 80

DSD: Directive 67/548/EEC. CLP: Regulation No. 1272/2008.

M: M-factor

vPvB: very persistent and very bioaccumulative substance.

PBT: persistent, bioaccumulative and toxic substance.

#: This substance has been assigned Community workplace exposure limit(s).

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume. *Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Composition comments

The full text for all R- and H-phrases is displayed in section 16.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial

respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper

respiratory medical device. Call a poison center or doctor/physician.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth thoroughly.

Most important

symptoms/effects, acute and

delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

May cause respiratory irritation. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment

needed

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show

the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Keep victim under observation. Keep victim warm.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

ecautions for firefighters

hting In case of fire and/or explosion do not breathe fumes. If tank, rail car or tank truck is involved in a fire,

ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions. ALWAYS stay away from tanks engulfed in flame. Move containers from fire area if you can do so without risk. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. For massive fire in cargo area, use unmanned hose

holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methodsUse standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards Combustible liquid.

Material name: Marine Super Cut Compound

1674 Version #: 08 Revision date: 11-04-2025 Issue date: 04-18-2023

rial name: Marine Super Cut Compound SDS CANADA

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. All equipment used when handling the product must be grounded. Do not breathe mist/vapors. Do not taste or swallow. Avoid contact with eyes. Avoid contact with skin. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Keep away from heat, sparks and open flame. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

Value

200 ma/m3

Form

Non-aerosol.

8. Exposure controls/personal protection

Occupational exposure limits

Components

KEROSENE (CAS

8008-20-6)							
Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended							
Components	Туре	Value	Form				
KEROSENE (CAS 8008-20-6)	TWA	200 mg/m3	Vapor.				
propane-1,2,3-triol (CAS 56-81-5)	TWA	10 mg/m3	Mist.				

Type

TWA

Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances Workers Compensation Board, as amended

Components	Туре	Value	Form
propane-1,2,3-triol (CAS 56-81-5)	TWA	3 mg/m3	Respirable mist.
		10 mg/m3	Total mist
Canada. Manitoba OELs (Reg. 2	17/2006, The Workplace Safety	And Health Act), as amended	
Components	Туре	Value	Form
KEROSENE (CAS 8008-20-6)	TWA	200 mg/m3	Non-aerosol.

1674 Version #: 08 Revision date: 11-04-2025 Issue date: 04-18-2023

SDS CANADA

Canada. New Brunswick OELs: Threshold Limit Values (TLVs) Based on the 1991 and 1997 ACGIH TLVs and BEIs

Publication (New Brunswick Regulation 91-191)

 Components
 Type
 Value
 Form

 KEROSENE (CAS
 TWA
 200 mg/m3
 Non-aerosol.

8008-20-6)

Canada. Ontario OELs (Regulation 833, Control of Exposure to Biological or Chemical Agents), as amended Components

Type

Value

Form

KEROSENE (CAS TWA 200 mg/m3 Non-aerosol.

8008-20-6)

Canada. Quebec OELs (Regulation respecting occupational health and safety, v. S-2.1, r.13), as amended

 Components
 Type
 Value
 Form

 KEROSENE (CAS 8008-20-6)
 TWA
 200 mg/m3

 propane-1,2,3-triol (CAS TWA 10 mg/m3 Mist.
 Mist.

56-81-5)

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996; Table 21), as amended

Components Form KEROSENE (CAS 15 minute 250 mg/m3 Vapor. 8008-20-6) 8 hour 200 mg/m3 Vapor. propane-1,2,3-triol (CAS 15 minute 20 mg/m3 Mist. 56-81-5) 8 hour 10 mg/m3 Mist.

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelines

Canada - Alberta OELs: Skin designation

KEROSENE (CAS 8008-20-6)

Can be absorbed through the skin.

Canada - Manitoba OELs: Skin designation

KEROSENE (CAS 8008-20-6) Danger of cutaneous absorption

Canada - Ontario OELs: Skin designation

KEROSENE (CAS 8008-20-6)

Can be absorbed through the skin.

Canada - Quebec OELs: Skin designation

KEROSENE (CAS 8008-20-6)

Can be absorbed through the skin.

Canada - Saskatchewan OELs: Can be absorbed through the skin.

KEROSENE (CAS 8008-20-6)

Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

KEROSENE (CAS 8008-20-6) Danger of cutaneous absorption

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Ensure adequate

ventilation, especially in confined areas. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Not available.

Skin protection

Hand protection Not available.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection Not available.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and

protective equipment to remove contaminants.

9. Physical and chemical properties

Physical state Liquid.

Form Liquid. Cream. Off-white. Color

Odor Hydrocarbon-like.

Melting point/freezing point Boiling point or initial boiling point and boiling range

68 °F (20 °C) estimated 347 °F (175 °C) estimated

Not applicable. **Flammability**

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available.

145.0 °F (62.8 °C) Flash point

410 °F (210 °C) estimated **Auto-ignition temperature**

Decomposition temperature Not available.

8.5 pН

Kinematic viscosity Not available.

Solubility

Not available. Solubility (water) **Partition coefficient** Not available.

(n-octanol/water) (log value)

Vapor pressure 0.28 hPa estimated

Density and/or relative density

10.64 lbs/gal Density Not available. Vapor density **Particle characteristics** Not available.

Other information

Not explosive. **Explosive properties**

Flammability class Combustible IIIA estimated

Oxidizing properties Not oxidizing. 225000 cP **Viscosity** Viscosity temperature 68 °F (20 °C)

VOC 16.95 % By Weight

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Material is stable under normal conditions. **Chemical stability**

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Contact with incompatible materials.

Strong oxidizing agents. Chlorine. Incompatible materials

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Under normal conditions of intended use, this material is not expected to be an inhalation hazard.

Skin contact No adverse effects due to skin contact are expected.

Causes serious eye irritation. Eve contact

May be harmful if swallowed. May cause discomfort if swallowed. However, ingestion is not likely to Ingestion

be a primary route of occupational exposure.

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Exposure may cause temporary irritation, redness, or discomfort.

Material name: Marine Super Cut Compound 5/8 1674 Version #: 08 Revision date: 11-04-2025 Issue date: 04-18-2023

Information on toxicological effects

Acute toxicity

Components Species Test Results

KEROSENE (CAS 8008-20-6)

Acute Dermal

LD50 Rat > 2000 mg/kg

Inhalation

LC50 Rat > 5200 mg/m3, 4 Hours

propane-1,2,3-triol (CAS 56-81-5)

Acute Inhalation

LC50 Rat > 570 mg/m3, 1 Hours

Oral

LD50 Rat 5.57 g/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Canada - Alberta OELs: Irritant

propane-1,2,3-triol (CAS 56-81-5) Irritant

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are mutagenic

or genotoxic.

Carcinogenicity

ACGIH Carcinogens

KEROSENE (CAS 8008-20-6)

A3 Confirmed animal carcinogen with unknown relevance to

humans.

Canada - Manitoba OELs: carcinogenicity

KEROSENE (CAS 8008-20-6) Confirmed animal carcinogen with unknown relevance to humans.

Canada - Quebec OELs: Carcinogen category

KEROSENE (CAS 8008-20-6) Detected carcinogenic effect in animals.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard May be harmful if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful. May cause damage to organs through prolonged or repeated

exposure. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Species Test Results

propane-1,2,3-triol (CAS 56-81-5)

Aquatic Acute

Fish LC50 Rainbow trout, donaldson trout 51000 - 57000 mg/l, 96 hours

(Oncorhynchus mykiss)

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Material name: Marine Super Cut Compound

SDS CANADA

Partition coefficient n-octanol / water (log Kow)

-1.76 propane-1,2,3-triol

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

TDG

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to

Not established.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

Canadian regulations This product has been classified in accordance with the hazard criteria of the HPR and the SDS

contains all the information required by the HPR.

Controlled Drugs and Substances Act

Export Control List (CEPA 1999, Schedule 3)

Not listed

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Canada

Country(s) or region Inventory name On inventory (yes/no)*

Canada Domestic Substances List (DSL) Yes

Non-Domestic Substances List (NDSL)

Material name: Marine Super Cut Compound 1674 Version #: 08 Revision date: 11-04-2025 Issue date: 04-18-2023 No

Country(s) or region Inventory name On inventory (yes/no)*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

04-18-2023 Issue date **Revision date** 11-04-2025

Version # 80

References **ACGIH**

EPA: AQUIRE database

NLM: Hazardous Substances Data Base

US. IARC Monographs on Occupational Exposures to Chemical Agents

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge, information

> and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Malco Products, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper

Yes

use.

Revision information Composition / Information on Ingredients: Component Summary

SDS CANADA Material name: Marine Super Cut Compound 8/8