malko •

SAFETY DATA SHEET

1. Identification

Product identifier MaxFinishing Polish

Other means of identification

Product Code 1635

Recommended use Compound, Polishing Creme

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Malco Products, Inc.
Address 361 Fairview Ave
Barberton, OH 44203

United States

Telephone Phone 800-253-2526

Fax 330-753-2025

Website www.malcopro.com
E-mail msdsinfo@malcopro.com
Contact person Technical Department

Emergency phone number Phone 1-800-424-9300

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 4Health hazardsAcute toxicity, oralCategory 5

Acute toxicity, inhalation Category 5
Serious eye damage/eye irritation Category 2A
Specific target organ toxicity, repeated Category 2

exposure

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Combustible liquid. May be harmful if swallowed. Causes serious eye irritation. May be harmful if

inhaled. May cause damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention Keep away from flames and hot surfaces-No smoking. Do not breathe mist or vapor. Wash

thoroughly after handling. Wear protective gloves/eye protection/face protection.

ResponseIF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical

advice/attention. In case of fire: Use appropriate media to extinguish.

Storage Store in a well-ventilated place. Keep cool.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

Combustible.

Material name: MaxFinishing Polish

34.86% of the mixture consists of component(s) of unknown acute dermal toxicity. 24.86% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 34.86% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Distillates (Petroleum), Hydrotreated Light		64742-47-8	10 - < 20
dialuminum;oxygen(2-)		1344-28-1	5 - < 10
Solvent Naphtha (Petroleum), Medium Aliph.		64741-65-7	5 - < 10
propane-1,2,3-triol		56-81-5	1 - < 3
1,3-bis(hydroxymethyl)-5,5-dimethyli midazolidine-2,4-dione		6440-58-0	< 0.2
sodium;hydroxide		1310-73-2	< 0.1
Other components below reportable I	evels		70 - < 80

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

InhalationIf breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Do not induce vomiting without advice from poison control center. If vomiting occurs,

keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you

feel unwell.

Most important symptoms/effects, acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media

Water fog. Alcohol resistant foam. Dry chemical powder. Dry chemicals. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards Combustible. Combustible liquid.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.

Material name: MaxFinishing Polish SDS US

Methods and materials for containment and cleaning up

Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Keep away from open flames, hot surfaces and sources of ignition. Do not breathe mist or vapor. Do not taste or swallow. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. When using, do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep away from heat and sources of ignition. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers.

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	Туре	Value	Form
dialuminum;oxygen(2-) (CAS 1344-28-1)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
propane-1,2,3-triol (CAS 56-81-5)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
sodium;hydroxide (CAS 1310-73-2)	PEL	2 mg/m3	
US. ACGIH Threshold Limit Values Components	s (TLV) Type	Value	
sodium;hydroxide (CAS 1310-73-2)	Ceiling	2 mg/m3	
NIOSH. Immediately Dangerous to	Life or Health (IDLH) Values,	as amended	
Components	Туре	Value	
sodium;hydroxide (CAS 1310-73-2)	IDLH	10 mg/m3	
US. NIOSH: Pocket Guide to Chem	nical Hazards Recommended I	Exposure Limits (REL)	
Components	Туре	Value	
sodium;hydroxide (CAS 1310-73-2)	Ceiling	2 mg/m3	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Ū

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece.

Material name: MaxFinishing Polish

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear suitable protective clothing. Use of an impervious apron is recommended.

Chemical respirator with organic vapor cartridge and full facepiece. Respiratory protection

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

General hygiene considerations

When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking.

Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid.

Form Liquid. Viscous. Color Light grey Pina Colada Odor Not available. **Odor threshold**

Hq 8.5

2741 °F (1505 °C) estimated Melting point/freezing point 661.81 °F (349.89 °C) estimated Initial boiling point and boiling

range

145.0 °F (62.8 °C) >145 Flash point

Evaporation rate Not available. Not applicable. Flammability (solid, gas) Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available.

Vapor pressure -0.01 hPa estimated

Not available. Vapor density Not available. Relative density

Solubility(ies)

Solubility (water) Not available. Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 739 °F (392.78 °C) estimated

Decomposition temperature Not available. **Viscosity** 20000 cP Viscosity temperature 68 °F (20 °C)

Other information

Density 8.67 lbs/gal **Explosive properties** Not explosive.

Flammability class Combustible IIIA estimated

Kinematic viscosity 31853 cSt 68 °F (20 °C) Kinematic viscosity

temperature

Oxidizing properties Not oxidizing. VOC 5 % By Weight

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. **Chemical stability**

1635 Version #: 19 Revision date: 10-28-2025 Issue date: 10-28-2025

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash Conditions to avoid

point. Contact with incompatible materials.

Incompatible materials

Acids. Strong oxidizing agents. Chlorine.

Hazardous decomposition products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May be harmful if inhaled. May cause damage to organs through prolonged or repeated exposure by

inhalation.

Skin contact No adverse effects due to skin contact are expected.

Eye contact Causes serious eye irritation. Ingestion May be harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Information on toxicological effects

Acute toxicity May be harmful if inhaled. May be harmful if swallowed.

Test Results Components **Species**

1,3-bis(hydroxymethyl)-5,5-dimethylimidazolidine-2,4-dione (CAS 6440-58-0)

Acute

Oral

LD50 Rat 2 - 3.65 g/kg

dialuminum;oxygen(2-) (CAS 1344-28-1)

Acute Oral

LD50 Rat > 5000 mg/kg

propane-1,2,3-triol (CAS 56-81-5)

Acute Inhalation

LC50 Rat > 570 mg/m3, 1 Hours

Oral

LD50 Rat 5.57 g/kg

sodium; hydroxide (CAS 1310-73-2)

Acute

Dermal

LD50 Rabbit 1350 mg/kg

Oral

LD50 Rat 140 - 340 mg/kg

Prolonged skin contact may cause temporary irritation. Skin corrosion/irritation

Serious eye damage/eye

Causes serious eye irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

No data available to indicate product or any components present at greater than 0.1% are mutagenic Germ cell mutagenicity

or genotoxic.

Not classifiable as to carcinogenicity to humans. Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

SDS US Material name: MaxFinishing Polish

^{*} Estimates for product may be based on additional component data not shown.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Not an aspiration hazard. **Aspiration hazard**

Chronic effects May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be

harmful.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components **Species Test Results**

Distillates (Petroleum), Hydrotreated Light (CAS 64742-47-8)

Aquatic

Acute

LC50 Fish

Rainbow trout, donaldson trout

(Oncorhynchus mykiss)

2.9 mg/l, 96 hours

propane-1,2,3-triol (CAS 56-81-5)

Aquatic

Acute

LC50 Fish

Rainbow trout, donaldson trout

51000 - 57000 mg/l, 96 hours

(Oncorhynchus mykiss)

sodium; hydroxide (CAS 1310-73-2)

Aquatic

Acute

Crustacea EC50 Water flea (Ceriodaphnia dubia) 34.59 - 47.13 mg/l, 48 hours

Fish LC50 Western mosquitofish (Gambusia affinis) 125 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

propane-1,2,3-triol -1.76

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

Material name: MaxFinishing Polish 6/8

^{*} Estimates for product may be based on additional component data not shown.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to

Not established.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard,

29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

Classified hazard Flammable (gases, aerosols, liquids, or solids)

Acute toxicity (any route of exposure) categories

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Chemical name CAS number % by wt. 5 - < 10 dialuminum;oxygen(2-) 1344-28-1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

propane-1,2,3-triol (CAS 56-81-5)

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is

Other Flavoring Substances with OSHA PEL's

US state regulations not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region Inventory name On inventory (yes/no)* Canada Domestic Substances List (DSL) Yes

Non-Domestic Substances List (NDSL) Canada No United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

country(s).

Material name: MaxFinishing Polish SDS US

16. Other information, including date of preparation or last revision

10-28-2025 Issue date 10-28-2025 **Revision date**

Version # 19

Disclaimer Malco Products, Inc. cannot anticipate all conditions under which this information and its product, or

the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for

such material used in combination with any other materials or in any process, unless specified in the

Revision information Product and Company Identification: Alternate Trade Names

Material name: MaxFinishing Polish 8/8

1635 Version #: 19 Revision date: 10-28-2025 Issue date: 10-28-2025